

swissbit®

Product Fact Sheet

Industrial CFexpress Card

G2600 Series
CFexpress v2.0, Type B, 3D pSLC

Industrial Temperature Grade

Date: November 2, 2023
Revision: 1.00



Product Summary

1 Product Summary

- **Capacities:** 20 GBytes, 40 GBytes, 80 GBytes, 160 GBytes, 320 GBytes
- **Form Factor:** CFexpress™ Type B card (38.5mm x 29.6mm x 3.8mm)
- **Compliance:** CFexpress v2.00
- **Interface:** Gen3 x 2 Lanes
- Drive operates in x1 mode in x1 CFexpress Type B slots
- Drive operates in x2 mode in x2 CFexpress Type B slots
- **Command Sets:** Supports NVMe 1.3
- **Performance:**
 - Read Performance: Sequential Read up to 1,610 MBytes/s, Random Read 4K up to 138,000 IOPS
 - Write Performance: Sequential Write up to 924 MBytes/s, Random Write 4K up to 143,000 IOPS
- **Host Memory Buffer (HMB):** Support for increased random performance
- **Operating Temperature Range²:**
 - Industrial: -40 °C to 85 °C
- **Storage Temperature Range:** -40 °C to 85 °C
- **Operating Voltage:** 3.3V supply voltage
- **Low Power Consumption**
- **Power:**
 - Power States P0, P1, P2, P3 and P4
 - Thermal Throttling supported
- **Data Retention:** 10 Years @ Life Begin; 1 Year @ Life End, @40°C
- **High-Performance Processor with Integrated, Parallel Flash Interface Engines:**
 - Triple-Level Cell (TLC) 3D NAND Flash
 - LDPC Code ECC with up to 120 bit correction per 1 KByte page
- **High Reliability:**
 - Designed for Industrial and Automotive market
 - Ideal for applications like automation, embedded computing, gaming, IIoT and NetCom
 - Optimized for long life cycle that requires superior data retention as well as power fail safety
 - Mean Time Between Failure (MTBF): > 2,000,000 hours
 - Data Reliability: < 1 non-recoverable error per 10¹⁶ bits read
 - Number of insertion/removal cycles: up to 12,000

¹ The verification of host system and storage device compatibility is in customer's responsibility. Swissbit can provide guidance and support on request.

² Adequate airflow is required to ensure the drive temperature, as reported in the S.M.A.R.T. data, does not exceed CCTEMP (Critical Composite Temperature Threshold) reported in the "Identify Controller Data Structure"

2 Product Features

- Dynamic and Static Wear Leveling
- Subpage Mode Flash Translation Layer (FTL)
- Data Care Management
 - Active: Adaptive Read Refresh
 - Passive: Background Media Scan
- Lifetime Enhancements
 - Dynamic Bad Block Remapping
 - Write Amplification Reduction
- Power Fail Data Loss Protection
- Data set management support (TRIM)
- Active State Power Management (ASPM) Support
- In-Field Firmware Update³
- Enterprise-Grade Self-Monitoring, Analysis, and Reporting Technology (S.M.A.R.T.)
- Gold-Plated Connector (IPC-6012B Class 2 Compliant)
- End-to-End (E2E) Data Protection
- AES256 Encryption
- TCG Opal
- Life Cycle Management, Controlled "Locked" BOM
- RoHS / REACH Compliant
- Swissbit Device Manager (SBDM) Tool and SDK for SBDM (on request)



Order Information for G2600

Density	Part Number	Temp. Range	Flash Technology
20 GBytes	SG2600CE020GI-1TB1-1AB-STD	-40°C to 85°C	3D NAND Flash SLC-mode
40 GBytes	SG2600CE040GI-1TB1-1AB-STD		
80 GBytes	SG2600CE080GI-1TB2-1AB-STD		
160 GBytes	SG2600CE160GI-1TB2-1AB-STD		
320 GBytes	SG2600CE320GI-1TB2-1AB-STD		

Why Swissbit?

Swissbit is focused on the design, development, manufacture, and support of leading edge memory and storage solutions for the worldwide OEM/ODM marketplace. As a global supplier, Swissbit recognizes and addresses the higher level of application requirements of today's industrial, Netcom, and automotive customers by providing best-in-class products and services, with uncompromised attention to driving overall value and quality.

³ The support of In-Field FW update capabilities on host systems is recommended.